INSPECTION CERTIFICATE

| DELIVER TO JOB NAME JOB NO. P.O.NO. PRODUCT CODE SPECIFICATION Manuf No. Description Figure | AP0-2004- | -0010 | | | | | | • | 82-003-01-01 2020/06/04 |
|---|--------------|----------------|------------|----------------|-------|----------|-----------|----------|----------------------------|
| JOB No. P.O.No. PRODUCT CODE SPECIFICATION lanuf No. Description | | -0010 | | | | | | | |
| P.O.No. PRODUCT CODE SPECIFICATION Manuf No. Description | | -0010 | | | | | | | |
| PRODUCT CODE SPECIFICATION Manuf No. Description | | -0010 | | | | | | | 4 |
| SPECIFICATION Manuf No. Description | <u> </u> | | | | | | | 13 | ITZ |
| Manuf No. Description | <u> </u> | | | | | | | •••• | |
| Manuf No. Description | l | | | | | | | | |
| Description | | | | | MAIN | PARTS | | | |
| · | 102033028 | 32-003 | | | | | of parts | Materia | |
| Figure | 10K DUCT | ILE IRON GLO | BE VALVE S | CREWED ENDS | | BODY | | Gr. 60 | |
| Figure | | | | | 002 | BONNE | <u>:T</u> | Gr. 60 | -40-18 |
| Figure | | | | | | | | | |
| 0. | 10SJ1/2 | | | (5) | | | | | |
| Size | 1/2 | | | inch(B) | - | | | | |
| Quantity Valve No. | 36 | | | | | <u> </u> | | | |
| varve no. | | | | | | | | | |
| Item No. | 3 | | | | | | | | |
| Kiki No. | | | | | | - | | | |
| | 1 | | | | | | | | |
| TEST | 1 | | | | | | 1 | <u>'</u> | |
| Pressure test | Judge. | | | nd pressure | Item | . , | Judge. | Attache | |
| Shell | Good | Hydro | 2.1 | MPa | Mater | ial | Good | Materia | l Test Result |
| | Good | Air | 1.4 | MPa | Dimen | sion | Good | | |
| Seat | | Hydro | - | | Visua | l | Good | | |
| | Good | Air | 0.6 | MPa | Opera | tion | Good | | |
| | Good | ATT | 0.6 | IVIFa | Орета | . 1011 | 0000 | | |
| Back seat | | Hydro | - | | | | | | |
| | | Air | - | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | • | • | | | | | • | |
| NONDESTRUCTIV | | | | 1 | | | | | |
| Type of examina | ation and | judgement | | Attached she | et | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| DEMARKS. | | | | | | | | | |
| REMARKS | TEOT 51/ 11 | VDDALII 10 C.: | FII TEAT | 40 DEEN BESES | MED | | | | |
| REPRESENTATIVE | : IEST BY H | YDRAULIC SH | ELL TEST H | AS BEEN PERFOR | MED | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | R. Mig | yazawi | 4 |
| | | Witnessed | | _ | | | • | , | |

MATERIAL TEST RESULT

| MESSRS | | | UNIMECH ENGINEERING (M) SDN. BHD. | | | | | | | | | | | | | Certificate No. 1020330282-003-01-01-Z1 | | | | | |
|---|------------|--------------------|------------------------------------|--------------|----------|------------------|---------------------------------|-----------------------|---------------|--------|------|-----------------------------------|------|--------|--------------|--|--------------------|--------------|---|----------|--|
| JOB N | IAME | | | | | | | | | | | | | | 7 - | | | 2020/ | | | |
| JOB N | | | | | | | | | | | | | | | | | | | | - | |
| P.O.No. APO-2 PRODUCT CODE | | | 20-2004-0010 | | | | | | | | | | | | | | | 72 | | | |
| TROBE | , , , | 0002 | | | | | | | | | | | | | | | | | | | |
| Figur | re | 10SJ1/ | 2 | | | | | | | | | Valve N | lo. | | | | | | | | |
| Material ASTM A | | | | | | | | | | |). | 3 | | | | | | | | | |
| | | ge No. | | Display No. | | | | Name of Parts BODY | | | | | | | | - | | | | | |
| 1 138 2 13F | | | | | | BONNET | | | - { | | | | | | | | | | | | |
| 3 4 | | | | | | | | | | | | | | | | | | | | | |
| | IICA | AL COMP | OSITIO | ON % | | | | | | | | | | | | | | | | | |
| Eleme | ent | С | Si | Р | Mn | | | | | | | | | | | | | | | | |
| Sp | ec. | Min 3.00 | *Max 2.50 | Max 0.080 | | | | | | | | | | | | | | | | | |
| 1 | | 3.61 | 2.59 | 0.021 | | | | | | | | | | | | | | | | | |
| 2 | | 3.61 | 2.60 | 0.019 | 0.28 | ' | | | | | | | | | | | | | | | |
| 4 Eleme | an t | | | | | | | | | | 4 | | | | | | | | | | |
| | ec. | | | | | | | | | | 1 | | | | | | | | | | |
| 1 | <u> </u> | + | | | | | | | | | + | | | | + | | | | | | |
| 2 | | | | | | | | | | | | | | | | | | | | | |
| 3 4 | | | | | | | | | | | | | | | | | | | | | |
| | 101 | I TEST | | | | | | | | | | IMF | PACT | TEST | | | | | | | |
| ltem Unit | + | | | | | ensile st IPa | r.Yield s MPa | | Elongati % | on | | | | | | | | | | | |
| Spec. | | | | | | lin | Min | | Min | | | | | | | | | | | | |
| 1 | + | | | | | 15 130 | 275 281 | | 18 21 | | | | | | | | | | | | |
| 2 | | | | | | 130 | 282 | | 21 | | | | | | | | | | | | |
| 3 4 | | | | | | | | | | | | | | | | | | | | | |
| Item | Тна | ardness | Micros | structure | <u>_</u> | | <u> </u> | | <u> </u> | | | | T | | | T | | T | | | |
| Unit | HE | 3 | % | | | | | | | | | | 4 | | | | | | | | |
| Spec. | | 143 Min 187 90 | | | | | | | | | | | | | | | | | | | |
| 1 | | | | | | | | | | | | | | | | | | | | | |
| 2 | 3 | | 90 | | | | | | | | | | | | | | | | | | |
| 4 | <u> </u> | | | | | | | | | | | | | | | | | | | | |
| | TR oec. | <u>EATMEN</u> T | I C | | | | | | | | Т | | | | | | | | | | |
| 1 | · | I | | | | | | | | | T | | | | | | | | | | |
| 2 | | | | | | | | | | | | | | | | | | | | | |
| 4 | N | | | | | • | | - - | | | | | | | | | ۸ : | 0 | | | |
| N:Normalizing A:Annealing WQ:Water Quenching OQ:Oil Quenching | | | | | | <u> </u> | T:Tempering WC:Water Cooling | | | | | Q:Quenching FC:Furnace Cooling | | | | | Cooling ution T | g reatmen | t | | |
| REMA | RKS | 3 | - | | | _ | | | | | | | | | | | | | | | |
| * Eve | ery 204 | 0.01% F Type 2 | reduc | ction e | nable | es 0.08% | Si inc | creas | se each | withir | n tl | he maxim | num | 2.75%. | | | | | | | |
| -11102 | _0-7 | 1300 2 | · <u>~</u> | | | | | | | | | | | | | | | | | | |
| L | | | | | | | | | | | _ | | | | | | | | | | |
| | | | | | | | | | | | | | K | m. | iya | zai | va | | | | |
| | | | Reviewed by Reviewed by KiTZ COR | | | | | | | | | | | |) R Δ | Tic | NC NC | | | | |
| | | | | , r | GV I CN | icu by | | | | | | | | QC | Manag | er | | • | | | |