INSPECTION CERTIFICATE

MESSRS	UNIMECH ENGINEERING (M) SDN. BHD.	Certificate No.
		1020330282-034-01-01
DELIVER TO		Date : 2020/06/04
JOB NAME		
JOB No.		
P.O.No.	AP0-2004-0010	KIT2
PRODUCT CODE		
]

SPECIFICATION

Manuf No.	1020330282-034
Description	20K DUCTILE IRON GLOBE VALVE FLANGED ENDS
Figure	20SYB50
Size	50 mm(A)
Quantity	5
Valve No.	
Item No.	34
Kiki No.	

MAIN PARTS

No.	Name of parts	Material
001	BODY	Gr. 60-40-18
002	BONNET	Gr. 60-40-18

KITZ

TEST

Pressure test	Judge.	Inspectio	n fluid a	nd pressure
Shell	Good	Hydro	4.2	MPa
	Good	Air	2.8	MPa
Seat		Hydro	-	
	Good	Air	0.6	MPa
Back seat		Hydro	-	
		Air	-	
			-	

Judge.	Attached sheet
Good	Material Test Result
Good	
Good	
Good	
	Good Good Good

NONDESTRUCTIVE EXAMINATION

Type of examination and judgement	Attached sheet

REMARKS

REPRESENTATIVE TEST BY HYDRAULIC SHELL TEST HAS BEEN PERFORMED

Witnessed by

R. Miyazawa KITZ CORPORATION QC Manager

MATERIAL TEST RESULT

GB NAME Integration Integration Integration Integration GB No. APO-2004-0010 APO-2004-0010 Integration Integration Integration APO-2004-0010 Integration Integration Integration Integration Still Parts Integration Integration Integration Still Parts Integration Integration Integration Integration Integration Integrati	MESSRS							_	cata No	
DB NO. APO-2004-0010 RODUCT CODE		UNIMECH ENGINEERING (M) SDN. BHD.				Certificate No. 1020330282-034-01-01-Z1				
I.O. No. APO-2004-0010 KCICZ ROUGE CODE Ingure 203Y850 Valve No. Material IASTM A 385 Gr. 60-40-18 Material IASTM A 385 Gr. 60-40-18 Material IASTM A 385 Gr. 60-40-18 Ltem No. 1135 1 138 2 137 3 0 Spec. Nin / Max Max Image: Spec. Nin / Max Max Image: Spec. Nin / Max Max Image: Spec. Nin / Max Max 1 Spec. Nin / Max Max Image: Spec. Nin / Max Image: Spec. Nin / Min / Min Image: Spec. Nin / Min / Min <td>JOB NAME</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Date :</td> <td>2020/06/04</td> <td></td>	JOB NAME							Date :	2020/06/04	
Indure Documentary Valve No. Interial IASTM A 395 Gr. 60-40-18 Itan No. Display No. Name of Parts 14 1 138 BODY Itan No. 34 21 13F BODY Itan No. 34 Charge No. Display No. Nome of Parts Itan No. 1 138 BODY Itan No. 34 Charge No. Sec. Nin Itan No. Spec. Nin Itan No. 14 Spec. Itan No. 14 14 14 Spec. Itan No. Itan No. 14 14 Spec. Itan Nin Itan Nin 14 14 Spec. Itan Nin Itan Nin 14 14 Spec.	JOB No.	4.00.0004.00	24.0							
Indure Documentary Valve No. Interial IASTM A 395 Gr. 60-40-18 Itan No. Display No. Name of Parts 14 1 138 BODY Itan No. 34 21 13F BODY Itan No. 34 Charge No. Display No. Nome of Parts Itan No. 1 138 BODY Itan No. 34 Charge No. Sec. Nin Itan No. Spec. Nin Itan No. 14 Spec. Itan No. 14 14 14 Spec. Itan No. Itan No. 14 14 Spec. Itan Nin Itan Nin 14 14 Spec. Itan Nin Itan Nin 14 14 Spec.	P.U.NO. PRODUCT CODE	AP0-2004-00	010							
Interial ASTM A 395 Gr. 60-40-18 Item No. 34 Charge No. Display. No. Name of Parts 1 38 1 138 BONVET Item No. 34 SHEMICAL COMPOSITION % Item No. Item No. 1 Spec. Nin Yaka Item No. Item No. 1 3. 6ft 2. 59 0.021 0.26 Item No. Item No. 1 3. 6ft 2. 59 0.021 0.26 Item No. Item No. 2 3. 6ft 2. 59 0.021 0.26 Item No. Item No. Item No. 1 3. 6ft 2. 59 0.021 0.26 Item No. Item No. Item No. Item No. 2 3. 6ft 2. 59 0.021 0.26 Item No.	TRODUCT CODE							•		
Interial ASTM A 396 Gr. 60-40-18 Item No. 34 Charge No. Display No. Name of Parts 1 38 1 138 BONY BONY 1 34 213F BONNET BONNET 1	<u></u>									
Instruction Asso OI OU Name of Parts 1 138 BONNET BONNET 1 138 BONNET BONNET 2 137 BONNET BONNET 3 00 2.50 0.080 Image of Parts 1 3.00 2.50 0.080 Image of Parts Spec. Min Image of Parts Image of Parts Spec. Min Image of Parts Image of Parts 2 3.00 2.50 0.020 Image of Parts 2 3.61 2.50 0.021 Image of Parts 2 3.61 2.50 0.021 Image of Parts 2 3.61 2.50 0.010 0.29 3 Image of Parts Image of Parts Image of Parts 2 3.61 2.50 0.010 0.29 3 Image of Parts Image of Parts Image of Parts 2 Image of Parts Image of Parts Image of Parts 3 Image of Parts Image of Parts Image of Parts <td></td>										
1 138 BODY 2 13F BONNET Litement C Si P Mn Spec. Min Max Max Max 1 3.61 2.50 0.020 Max Max 1 3.61 2.50 0.021 0.26 Max Max 1 3.61 2.50 0.021 0.26 Max Max Max 1 3.61 2.50 0.021 0.26 Max Max Max 1 2.3 0.019 0.29 Max Max Max Max 1 2.50 0.021 0.26 Max Max Max Max 1 2.3 1 Max Max Max Max Max Max 1 1 Max Max Max Max Max Max Max Max 1 Max 1 Max <t< td=""><td></td><td></td><td></td><td>Nove of</td><td>Deste</td><td>TTEM NO.</td><td>34</td><td></td><td></td><td></td></t<>				Nove of	Deste	TTEM NO.	34			
2 13F BONNET HEMICAL COMPOSITION % Image: Composition of the stress of the			Tay NO.							
4 : : : CHENICAL COMPOSITION % : : : Spec. Min Max Max Image: Composition (Composition (Compos										
DHEMICAL COMPOSITION % Itement C Si P Mn Spec. Min Max Image: Spec. Min P Image: Spec. Min P 1 3.61 2.59 0.021 0.26 2 3.61 2.60 0.080 Image: Spec. Min P Image: Spec. Min P 1 3.61 2.60 0.019 0.29 Image: Spec. Min P Image: Spec. Min P 1 2 3.61 2.57 1 Image: Spec. Min P Image: Spec. Min P 1 Image: Spec. Min P MPa MPa % Image: Spec. Min P Image: Spec. Min P Image: Spec. Min P 1 415 275 18 Image: Spec. Min P Image: Spec. Min P Image: Spec. Min P 1 430 281 21 Image: Spec. Min P Image: Spec. Min P Image: Spec. Min P 1 143 90 Image: Spec. Min P Image: Spec. Min P<	3									
Itement C Si P Mn Image: Construct of the state of th										
Spec. Min *Max Max Max Max Max 3.00 2.50 0.080 0.21 0.26 0.01 0.26 0.01 0.26 0.01 0.26 0.01 0.26 0.01 0.26 0.01 0.26 0.01 0.26 0.01 0.26 0.01 0.26 0.01 0.26 0.01 0.26 0.01 0.26 0.01 0.01 0.26 0.01<			Mo							
3.00 2.50 0.080 Image: Construction of the second s										
2 3.61 2.60 0.019 0.29	3.00	2.50 0.080								
3										
4 1	3 3.61	2.60 0.01	0.29							
Spec. Image: Contract of the stress of the str	4									
Image: 1 Image										
2 3										
34 1 <th1< th=""> 1 1 1<td>1</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></th1<>	1									
4	2									
tem Tensile str. Yield str. Elongation Imit Imit MPa MPa % Imit Imit MPa MPa % Imit Imit MPa Min Min <th< td=""><td>4</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></th<>	4									
Init MPa MPa % Image: Construct of the second secon	TENSION TEST					IMPA	CT TEST			
Spec. Min Min </td <td>ltem</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	ltem									
415 275 18 1 1 430 281 21 1 2 430 282 21 1 1 1 HB % 1 1 1 1 1 143 90 1 1 1 1 1 1 143 90 1										
1 430 281 21 <t< td=""><td>spec.</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>	spec.									
3 4	1		430	281	21					
4	2		430	282	21					
Init HB % Image: Market of the second	4									
Init HB % Image: Market of the second		Microstructu	re l	 T				1	1	I
187 90 90 1 143 90 2 143 90 3 4 90 IEAT TREATMENT °C 90 Spec. 1 1 2 3 4 N:Normalizing A:Annealing T:Tempering Q:Quenching AC:Air Cooling	Unit HB									
1 143 90 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>										
2 143 90										
4 IEAT TREATMENT °C Spec. 1 2 3 4 N:Normalizing A:Annealing T:Tempering Q:Quenching AC:Air Cooling	2 143									
IEAT TREATMENT °C	3									
Spec. 1 2 3 4 N:Normalizing A:Annealing T:Tempering Q:Quenching AC:Air Cooling		 IT ° ^		1						
1 2 3 4 N:Normalizing A:Annealing T:Tempering Q:Quenching AC:Air Cooling	ISpec I	II U								
2 2 3 4 N:Normalizing A:Annealing T:Tempering Q:Quenching AC:Air Cooling	1									
4 V:Normalizing A:Annealing T:Tempering Q:Quenching AC:Air Cooling	2									
N:Normalizing A:Annealing T:Tempering Q:Quenching AC:Air Cooling	3 4									
	N:Normalizing A:Annealing		T:T	T:Tempering				-		
			WC:			ace Cooling	g ST:Solution Treatment			
				-	v					
* Every 0.01% P reduction enables 0.08% Si increase each within the maximum 2.75%. EN10204 Type 2.2	REMARKS	-								

Reviewed by

R. Miyazawa

KITZ CORPORATION QC Manager

We hereby certify that the articles listed above are satisfactory in accordance with the requirements of the standard and purchase order.