INSPECTION CERTIFICATE

| MESSRS | UNIMECH | ENGINEERING | (M) SDN. E | SHD. | | | | Certificate No. 1020329222-013-01- | 01 |
|---------------|---|---------------|-------------|----------------|--------|-------|----------|---------------------------------------|-----|
| DELIVER To | | | | | | | | Date : 2020/07/2 | |
| JOB NAME | | | | | | | | | |
| JOB No. | | | | | | | | | |
| P.O.No. | AP0-2004 | | | | | | | KIT | |
| PRODUCT CODE | (TR)TK <z< td=""><td>0P02>2</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></z<> | 0P02>2 | | | | | | | |
| SPECIFICATIO |)N | | | | MAIN | PARTS | | | |
| Manuf No. | 10203292 | 22-013 | | | | | f parts | Material | |
| Description | TYPE 600 ENDS | FORGED BRAS | SS BALL VAI | LVE SCREWED | | BODY | - parto | C 3771 BE | |
| Figure | TK <z0p02< td=""><td>>2</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></z0p02<> | >2 | | | | | | | |
| Size | 2 | | | inch(B) | | | | | |
| Quantity | 16 | | | | | | | | |
| Valve No. | | | | | | | | | |
| Item No. | 15 | | | | | | | | |
| Kiki No. | | | | | | | | | |
| TEST | | | | | | | | | |
| Pressure test | Judge. | Inspecti | on fluid a | nd pressure | Item | | Judge. | Attached sheet | |
| Shell | Good | Hydro | 6.18 | MPa | Materi | al | Good | Material Test Res | ult |
| | Good | Air | 0.6 | MPa | Dimens | sion | Good | | |
| Seat | | Hydro | - | | Visual | | Good | | |
| | Good | Air | 0.6 | MPa | Operat | ion | Good | | |
| Back seat | | Hydro | - | | | | | | |
| | | Air | - | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| NONDESTRUCT | IVE EXAMIN | ATION | | | | | <u> </u> | | |
| Type of exami | nation and | judgement | | Attached she | eet | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| DEMARKO | | | | | | | | | |
| REMARKS | /F TEAT 5\/ : | IVDDAIL 10 C. | FIL TEAT :: | 140 DEEN DEDES | DUED | | | | |
| REPRESENTATIV | E LEST BY F | HYDRAULIC SH | ELL TEST H | AS BEEN PERFOR | KMED | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | 1/1, | auate | |
| | | | | | | | N.K | wate | |
| | | Witnessed | by | _ | | Κi | TZ COi | RPORATION | |

MATERIAL TEST RESULT

| MESSRS | | UNIMECH ENGINEERING (M) SDN. BHD. | | | | | | | | | | | | Certificate No. 1020329222-013-01-01-Z1 | | | | | | |
|---|-------------|-----------------------------------|----------------------------|--------------|--|-----------|---------------|----------|------------------|---------------------------|----------|--------------------|-------------|--|---------|-------------------|-----|-----------|--|--|
| JOB NAME | | | | | | | | | | | | | | | | | | | | |
| JOB No. | | | | | | | | | | | | | | | | | _ | | | |
| | 0.No | | | APO-2004-007 | | | | | | | | | | | | 14 | | 72 | | |
| PRODUCT CODE | | (TR)TK <z0p02>2</z0p02> | | | | | | | | | | | | | •• | | | | | |
| Figure TK <z0p0< td=""><td colspan="9">02>2 Valve No.</td><td></td><td></td><td></td><td></td><td></td><td></td></z0p0<> | | | 02>2 Valve No. | | | | | | | | | | | | | | | | | |
| | Mat | eri | erial JIS H 3250 C 3771 BE | | | | | | | | 15 | | | | | | | | | |
| _ | | rge | No. | Display No. | | | Name of Parts | | | | 1 | | | | | | | | | |
| | 1 270219 | | | | | BODY | OUY | | | | | | | | | | | | | |
| 2 3 | | | | | | | | į | | | | į | | | | | | | | |
| 4 | | | | | | | | <u> </u> | | | | <u>!</u> | | | | <u>!</u> | | | | |
| CH | IEM I | CAL | | OSITION % | | | | | | | | | | | | | | | | |
| 쁜 | emen | <u>t</u> | Cu 57.0 | Pb 1.0 | | | | | | | | | + | | | + | | | | |
| L | Sher | ; <u> </u> | 61.0 | 2.5 | | | | | | | | | | | | | | | | |
| 1 | | | 59.0 | 1.8 | | | | | | | | | | | | | | | | |
| 3 | | | | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | | | | |
| EI | emen | | Fe+Sn | | | Zn | | | | | | | | | | | | | | |
| Spec. Max 1.0 | | | Remainder | | | | | | | | | | | | | | | | | |
| 1 | | | 0.3 | | | REM. | | | | | | | | | | | | | | |
| 2 | | | | | | | | | | | | | | | | | | | | |
| 3 | | | | | | | | | | | | | | | | | | | | |
| _ | NS I | ON. | TEST | | | | | | | | | | IMPACT TEST | | | | | | | |
| Item | | Tensile str | | | | | | | | | | | | | | | | | | |
| Un | | | | | | | I/mm2 | | 9 | | | | | | | | | | | |
| l ob | Spec. | | | Min 315 | | Min 15 | | | | | | | | | | | | | | |
| 1 | Ì | | | | | | 134 | | | 33 | | | | | | | | | | |
| 3 | | | | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | | | | |
| Ιt | em | | | | | | | | | | | | | | | | | | | |
| Un | i t | | | | | | | | | | | | | | | | | | | |
| Sp | <u>e</u> c. | | | | | | | | | | | | | | | | | | | |
| 1 | \dashv | | | | | | | | | | | | | | | | | | | |
| 2 | | | | | | | | | | | | | | | | | | | | |
| 3 | | | | | | | | | | | | | | | | | | | | |
| | AT | ΓRE | ATMEN | Γ°C | | | | | | | | | | | | 1 | | | | |
| 1 | Spe | c. | | | | | | | | | | | | | | | | | | |
| 2 | | | | | | | | | | | | | | | | | | | | |
| 3 | | | | | | | | | | | | | | | | | | | | |
| 4 N:Normalizing A:Annealing T:Tempering Q:Quenching | | | | | | | | | | | AC:Ai | r Coolir | na | | | | | | | |
| WQ:Water Quench | | | ching | | | | | | WC:Water Cooling | | | FC:Furnace Cooling | | | | | | | | |
| | REMARKS | | | | | | | | | | | | | | | | | | | |
| JIS G 0415 2.2 | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | • | K.K | Λı ı. ~ | t | | | | |
| | | | | | | n: - | od b.: | | - | | | - | KIT. | <u> </u> | | <i>∕₩</i> ⊋∧┰¹ | ion | | | |
| Reviewed by KiTZ CORI | | | | | | | | | | Nanager Manager | \ | | | | | | | | | |