



**ARITA VALVE QUALITY & PRODUCT INSPECTION REPORT**

MODEL	MODEL NO.	PRESSURE	QTY	NORMINAL DIAMETER	DATE
ARITA SUS304 Sight Glass S/E W/O Flapper	ARV-108SE(J)	JIS 10K	7 pcs	DN50 (2")	14TH.DEC.2021

**PRESSURE TEST**

HYDROSTATIC SHELL TEST	
PRESSURE : 1.5 Mpa	
DURATION : 1 MINUTES	
LEAKAGE	OK

**RELATIVE STANDARD**

STANDARD	JIS 10K	BS21 (BSPT)
----------	---------	-------------

**MATERIAL CERTIFICATE**

DESCRIPTION	CHEMICAL COMPOSITION (%)										TENSILE Mpa	YIELD Mpa	ELONGATION %	REDUCE AREA%		
	PART	MATERIAL	HEAT NO.	C	Mn	P	S	Si	Cu	Ni					Cr	Mo
Body	CF8	N/A	0.07	1.42	0.03	0.004	1.76	1.31	8.44	18.26	0.45	0.08	495	210	38	-
Cap	CF8	N/A	0.05	1.31	0.03	0.006	1.85	0.47	8.29	18.26	0.29	0.09	495	210	38	-


REMARK: IN ACCORDANCE WITH EN 10204.3.1B

HEREBY, WE CERTIFY THAT THE NOMINATED PRODUCTS ARE QUALIFIED AND COMPLIANCE IN:

1. MAIN COMPONENTS OF NATIONAL STANDARD OR / RELATIVE CRITERION.

2. CONNECTION SIZE OF NATIONAL STANDARD OR / RELATIVE CRITERION.

3. QUEST OF CLIENT OR P.O. SPECIFIED



ARITA VALVE MFG. (M) SDN. BHD.