





ARITA VALVE QUALITY & PRODUCT INSPECTION REPORT

P/O NO	MODEL	MODEL NO.	PRESSURE	QTY	NORMINAL DIAMETER	DATE										
APO-2203-0090	SUS 316 1-Pc Disco Check Valve	ARV-106WT(U)	PN 40	80 pcs	DN80 (3")	15TH.MARCH.2022										
PRESSURE TEST																
HYDROSTATIC TEST FOR SHELL																
HYDROSTATIC LEAKAGE TEST																
PRESSURE : 60 Bar																
PRESSURE : 44 Bar																
DURATION : 1 MINUTES																
DURATION : 1 MINUTES																
LEAKAGE OK																
LEAKAGE OK																
RELATIVE STANDARD																
STANDARD	DIN 3202-3 K4															
MATERIAL CERTIFICATE																
CHEMICAL COMPOSITION (%)																
DESCRIPTION	TENSILE	YIELD	ELONGATION	REDUCE												
PART	MATERIAL	HEAT NO.	C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	TENSILE	YIELD	ELONGATION	REDUCE
													Mpa	Mpa	%	AREA%
Body	CF8M	-	0.02	1.13	0.03	0.002	0.35	-	10.1	18.0	2.2	-				
Disc	CF8M	-	0.02	0.67	0.03	0.006	0.65	-	10.1	18.7	2.1	-				
REMARK: IN ACCORDANCE WITH EN 10204.3.1B																
HEREBY, WE CERTIFY THAT THE NOMINATED PRODUCTS ARE QUALIFIED AND COMPLIANCE IN:																
1.MAIN COMPONENTS OF NATIONAL STANDARD OR / RELATIVE CRITERION.																
2.CONNECTION SIZE OF NATIONAL STANDARD OR / RELATIVE CRITERION.																
3.QUEST OF CLIENT OR P.O. SPECIFIED																
 																
ARITA VALVE MFG. (M) SDN. BHD.																